

OUTLASTING EXTINCTION

REDCO™

OUTRIGGER PADS

WITHSTANDING THE ELEMENTS

- Lightweight, 1/7th The Weight Of Steel
- Withstands Loads Up To 3000 psi
- Retains Its Physical Properties To -80°C
- Will Not Corrode, Rot, Or Rust
- High Impact & Wear Resistance
- No Water Absorption (remains lightweight in wet environments)
- Can Withstand Over 1,000,000 Lbs Of Compressive Load

Customizable - Call Us With Any Request.



**REDWOOD
PLASTICS**
INNOVATIVE SOLUTIONS IN PLASTIC

CONTACT US TODAY
CDN 1 800 667 0999
USA 1 866 733 2684
www.redwoodplastics.com

SINCE 1971

REDCO™ OUTRIGGER PADS

Save time, Save Money... Save Your Strength!



Lighter and longer lasting than plywood or steel, Redco™ Outrigger Pads stand up to harsh weather and extreme environments to protect you and your equipment from costly accidents.

Redco™ Outrigger Pads are available in **Redco™ UHMW**, **Redco™ Nylon** and **Anti-Slip Varieties**.

- Rope or Wire Handles Included
- SAFETY TEXTURING - Non Slip Varieties Available
- CUSTOM Sizes and Shapes Available
- Standard Sizes up to 84" WIDE

Standard Sizes

LOAD CAPACITY OF UHMW (pounds)		WIDTH	LENGTH	THICKNESS	WEIGHT (pounds)	SQ. IN
VERTICAL	45 ANGLE					
55,000	30,000	18"	18"	1"	11	324
60,000	35,000	22"	24"	1"	19	528
60,000	35,000	24"	24"	1"	20	576
62,000	40,000	24"	24"	2"	38	576
81,000	41,000	30"	30"	1"	31	900
85,000	43,000	30"	30"	2"	62	900
93,000	43,000	36"	36"	1"	45	1296
98,000	45,000	36"	36"	2"	90	1296
140,000	55,000	48"	48"	2"	160	2304



Gripping Cleats Available



Anti-Slip Surface Available

- Note:
- 8X10 outrigger leg applied under two separate loading conditions; 10,000 pounds vertically and 10,000 pounds with a 45 degree angle.
 - Redco Nylon Outrigger Pads have higher load capacities than UHMW.
 - Custom Sizes Available



CUSTOM DESIGN AND FABRICATION

Redwood Plastics supplies a wide range of high quality, custom components to solve a variety of problems including; shock, abrasion, noise, wear, & friction.

We work with you to develop valuable application solutions to reduce equipment wear, diminish maintenance costs and increase production.

www.redwoodplastics.com
sales@redwoodplastics.com

Call Your Local Representative Today



**REDWOOD
PLASTICS**
INNOVATIVE SOLUTIONS IN PLASTIC

CDN 1 800 667 0999
USA 1 866 733 2684

We cannot anticipate all conditions under which this information and our products or the products of other manufacturers in combination with our products may be used. We accept no responsibility for results obtained by the application of this or the safety and suitability of our products, whether alone or in combination with other products. Users are advised to make their own test to determine the safety and suitability of each such product or product combination for their own purposes. Unless otherwise agreed in writing, we sell the products without warranty, and buyers and users assume all responsibility and liability for loss or damage arising from the handling and use of our products, whether used alone or in combination with other products.
For most recent technical information, phone 360 225 1491 in USA or 604 607 6000 in Canada.

Printed in Canada

A Member of
PRISMA
Plastics International Inc.