



TOUGH FENDERS WITH TUFFKAST

PROTECT SHIPS AND VESSELS FROM IMPACT AND FRICTION



High Visibility
Better Tensile Strength
Low Moisture Absorption
Improved Impact Values
Better Compressive Strength
Low Coefficient of Friction (.15)
Higher Operating Temperatures




REDWOOD
PLASTICS AND RUBBER

SIX BRANCHES ACROSS NORTH AMERICA

Vancouver, BC
Prince George, BC
Edmonton, AB

Woodland, WA
Spokane, WA
Atlanta, GA



STRONG AND RESILIENT

Redco™ Tuffkast has a combination of strength and resilience resulting in a high performance plastic that offers excellent wear and abrasion resistance with rigidity, minimal water absorption and superior impact values. Ideal for harsh environments where excessive weight, water saturation, abrasion, shock and impact are factors.

TUFFKAST GRADES

TUFFKAST 025

- High impact resistance with tensile properties and bearing compressive properties.
- Recommended for applications where factors such as shock, abrasion, vibration, impact, load, and a harsh environment limit the suitability of traditional materials.

TUFFKAST 020 – Carriage Wheel Material

- Special formulation for sawmill carriage wheel applications.

TUFFKAST 015 – Oil Filled

- Liquid lubricant is impregnated within the polymer chain which offers excellent surface lubricity for wear resistance and a reduced co-efficient of friction.
- Withstands shock, vibration and loads up to 4,000 psi.
- Lowest moisture absorption of any of the Tuffkast or nylon materials.
- Primarily intended for marine applications.

TUFFKAST 010 – Solid Lubricant

- Combines the impact resistance of polyurethane with the wear resistance of a solid lubricant which results in the longest lasting material for aggressive industrial applications.
- Typically used for dynamic friction applications which are subjected to extreme stress and impact such as bearing blocks, torsion couplings, wear strips, etc.

CUSTOM DESIGN AND FABRICATION

Redwood Plastics has designed and fabricated a variety of solutions to shock, abrasion, noise, wear and friction for many industries, resulting in increased production, decreased maintenance costs and decreased down time, adding to your bottom line.

We cannot anticipate all conditions under which this information and our products or the products of other manufacturers in combination with our products may be used. We accept no responsibility for results obtained by the application of this or the safety and suitability of our products, whether alone or in combination with other products. Users are advised to make their own test to determine the safety and suit ability of each such product or product combination for their own purposes. Unless otherwise agreed in writing, we sell the products without warranty, and buyers and users assume all responsibility and liability for loss or damage arising from the handling and use of our products, whether used alone or in combination with other products. For most recent technical information, phone 1 833 381 1195.